



28, avenue Franklin Roosevelt – 69120 VAULX-EN-VELIN  
Tél : +33 (04).78.49.01.61 – Fax : +33 (04).78.49.12.59 - Email : [sofiplast@sofiplast.fr](mailto:sofiplast@sofiplast.fr)

## **Product Data Sheet ASP 126**

### **General information :**

- *Excellent resistance to chemical agents*
- *Very good resistance to bad weather conditions and UV*
- *Excellent di-electric resistance*
- *Excellent adherence to most substrates*
- *Very good properties for noise reduction and removal*
- *Very good resistance to shock and impact*
- *Working temperature - 30°C to + 100°C*
- *Coating thickness : from 150 to 400 microns depending on conditions and use*
- *Conforms to FDA and BGA regulations relating to coatings used in the FOOD sector*
- *Available in various colours*

### **Applications :**

- *ASP 126 coating is suitable for use on CONVEYOR and HANDLING equipment due to their mechanical properties, noise absorption and di-electric properties.*
- *ASP 126 coating is suitable for use on non-metallic CONVEYOR and STORAGE equipment to help avoid scratches and marks on their surfaces (carrier conveyors, baskets, grilles, hooks, pallets ...)*
- *ASP 126 coating is suitable for use on STORAGE equipment in outdoor or corrosive environments.*

The information contained in product sheet ASP 126\_2011 is for guidance purposes only. It may be subject to variation depending on the supply, nature and shape of the parts.